## EMT-600-SSH-220EU


**Magnetic**


Outdoor Stainless Steel Enclosure
Multi Tap: **12-15VAC**
Total Wattage: **600W max**
Input Voltage: **220V 50Hz**

www.emcod.com

**Conforms to UL STD. 1838**
**Certified to CSA**
**STD. C22.2 № 250.0, 250.7**






### Transformer

Temperature class B(130°C)
Input leads: Line cord
Output leads: Terminal Block
Magnetic manually reset secondary breaker 25A per circuit
Timer and photocell build in options

### Housing

The actual transformer 600W is encapsulated in the enclosure
The enclosure is Stainless Steel, NEMA 3R rated
Wiring compartment has 6 knockouts sizes for 3/8 inch screw cable connectors
Enclosure Temperature does not exceed 75°C at 45°C ambient and fully loaded
Dimensions (inch): H = 18.95, W = 6.58, D = 5.75
Weight (LBs): 2.8

### Electrical Parameters

| | | |
|---|---|---|
| Input Voltage: | **220V 50Hz** | |
| Max. input current at full load: | **5A** | |
| Output voltage without load: | **12/ 13.2/ 14/ 15.1VAC** | |
| Output voltage fully loaded: | **11.3/ 12.5/ 13.1/ 14.4VAC** | |
| Max. Total Wattage: | **600W** | Max. per circuit: **300W** |
| Max. Output Current: | **25/ 23/ 21/ 20A** per circuit. | |
| Efficiency: | **93%** | |
| Load regulation: | **0.04%** | |

**Mailing Address: 646 Flinn Ave. Unit B, Moorpark , CA 93021 Tech support: Arik Nirenberg phone: 818-904-3309**
**Fax: 818 904 3327 info@emcod.com techsupport@emcod.com**