

MLS100S12AC

Magnetic Phase cut Dimmable LED AC Driver

Outdoor Stainless Steel Enclosure

Single Circuit: **12VAC**

Total Wattage: **100W max**


Input Voltage: **120V 60Hz**



www.emcod.com



Conforms to UL STD. 2108
Certified to CSA
STD. C22.2 No 250.0
model EM100
[Link to certification](#)



Transformer

Dimmable with compatible dimmers please refer to list on emcod.com

Temperature class B(130°C)

Input leads are 18AWG 600V

Output leads are 18AWG 300V

Leads max. operational temperature is 105°C

Thermal manually reset primary breaker 2A

Thermal manually reset secondary breaker 13A

Housing

The actual transformer 100W is encapsulated in the enclosure

The enclosure is Stainless Steel, Dry, Damp and Wet Location rated

Wiring compartment has 5 knockouts sizes for 3/8 inch screw cable connectors

Enclosure Temperature does not exceed 75°C at 45°C ambient and fully loaded

Dimensions (inch): H = 8.13, W = 3.93, D = 1.59

Weight (LBs): 0.4

Electrical Parameters

Input Voltage: **120V 60Hz**

Max. input current at full load: **1A**

Output voltage without load: **13.5VAC**

Output voltage fully loaded: **11.5VAC**


Max. Total Wattage: **100W**

Max. Output Current: **8.3A**

Efficiency: **85%**

Load regulation: **0%**

Ripple: **0%**



Mailing Address: 646 Flinn Ave. Unit B, Moorpark , CA 93021 Tech support: Arik Nirenberg phone: 818-904-3309

Fax: 818 904 3327 techsupport@emcod.com