

## ECC-020-UD

### Constant Current UNIV 5 in 1 dimming

Plastic Suitable For Dry And Damp Location Enclosure

Single Circuit: **3-42VDC**

Total Wattage: **20W max**


Input Voltage: **100-277V 50/60Hz**



www.emcod.com



Conforms to UL STD. 8750  
Certified to CSA  
STD. C22.2 No 250.13



### Transformer

Dimmable with triac forward and reverse phase, 0/1-10V , resistor, PWM  
Temperature class B(130°C)

### Housing

The actual transformer 20W is encapsulated in the enclosure  
The enclosure is Plastic suitable for dry and damp location, IP20, wire  
compartment is optional rated  
Enclosure Temperature does not exceed 65°C at 45°C ambient and fully  
loaded

Dimensions (inch): H = 1.7, W = 5.7, D = 0.8

Weight (LBs): 0.33

### Electrical Parameters

Input Voltage: **100-277V 50/60Hz**

Max. input current at full load: **0.3A**

Output voltage without load: **42VDC**

Output voltage fully loaded: **VDC**

Max. Total Wattage: **20W**

Max. Output Current: **0.7A**

Efficiency: **78%**

Output	Rated current (mA)	700mA	600mA	550mA	500mA	450mA	400mA	350mA	250mA
		TTT	TTT	TTT	TTT	TTT	TTT	TTT	TTT
Current Tolerance		±5%							
DC Voltage		3-29V	3-33V	3-26V	3-40V	3-42V	3-42V	3-42V	3-42V
Rated power		20.3W	19.8W	19.8W	20W	18.9W	16.8W	14.7W	10.5W

Mailing Address: 646 Flinn Ave. Unit B, Moorpark , CA 93021 Tech support: Arik Nirenberg phone: 818-904-3309

Fax: 818 904 3327 info@emcod.com techsupport@emcod.com