

ECV200-12DC

Electronic EV

Outdoor Aluminum With Wire Compartment Enclosure


Single Circuit: **12VDC 400Hz**

Total Wattage: **200W max**

Input Voltage: **120V 50/60Hz**



Conforms to UL STD. 1012
Certified to CSA
STD. C22.2 No 107.1



Transformer

Dimmable with any ELV, MLV, CL, forward or reverse phase.

Input leads are 18AWG 600V

Output leads are 18AWG 300V

Leads max. operational temperature is 105°C

Housing

The actual transformer 200W is encapsulated in the enclosure

The enclosure is Aluminum with wire compartment, IP 67 rated

Wiring compartment has 4 knockouts sizes for 3/8 inch screw cable connectors

Enclosure Temperature does not exceed 70°C at 45°C ambient and fully loaded

Dimensions (inch): H = 14.3, W = 3.03, D = 2.24

Weight (LBs): 0.4

Electrical Parameters

Input Voltage: **120V 50/60Hz**

Max. input current at full load: **3.6A**

Output voltage without load: **12.2VDC**

Output voltage fully loaded: **12VDC**


Max. Total Wattage: **200W**

Max. Output Current: **16.7A**

Efficiency: **85%**

Load regulation: **1%**

Ripple: **10%**



Mailing Address: 646 Flinn Ave. Unit B, Moorpark, CA 93021 Tech support: Arik Nirenberg phone: 818-904-3309

Fax: 818 904 3327 info@emcod.com techsupport@emcod.com